


# REPORT DOCUMENTATION PAGE

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

**PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

AFRL-SR-AR-TR-05-

0360

1. REPORT DATE (DD-MM-YYYY) 05082005		2. REPORT TYPE Final Report		3. DATES COVERED (From - To) 01 Mar 2001 - 28 Feb 2005	
4. TITLE AND SUBTITLE  Novel Passive Vibration Control Methods for Aerostructures				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER  F49620-01-1-0208	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)  Professor Lawrence A. Bergman				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Department of Aerospace Engineering 306 Talbot Lab, MC-236 104 South Wright Street Champaign IL 61820-6242				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) USAF/AFRL AFOSR 875 North Randolph Street Arlington VA 22203 				10. SPONSOR/MONITOR'S ACRONYM(S)  AFOSR	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT  Distribution Statement A. Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT  The principal goals of this project were the further analysis and the experimental demonstration of the phenomenon of nonlinear energy pumping (targeted energy transfer), in which the vibration of a structure following a transient disturbance is irreversibly localized to a preferred subsystem, termed a nonlinear energy sink, and dissipated there. The occurrence of energy pumping depends on the essential nonlinearity of the sink stiffness; that is, this stiffness must be nonlinearizable, with no linear term in its force-displacement relation. Two types of nonlinear energy sink (NES) have been investigated: Configuration I, in which the sink mass is coupled weakly and linearly to the primary structure and essentially nonlinearly to ground; and Configuration II, in which the coupling to the primary structure is essentially nonlinear but there is no connection of the sink to ground.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (Include area code)
U	U	U	UU	11	

**Final Report to AFOSR**

**5 August 2005**

**Principal Investigators**

Prof. Lawrence A. Bergman  
Department of Aerospace Engineering  
306 Talbot Lab, MC-236  
104 South Wright Street  
Phone 217-333-4970, Fax 217-244-0720  
Email lbergman@uiuc.edu

Prof. Alexander F. Vakakis  
Department of Mechanical and Industrial Engineering  
Mechanical Engineering Building, MC-244  
1206 West Green Street  
Email avakakis@uiuc.edu

University of Illinois  
Urbana, IL 61801

**NOVEL PASSIVE VIBRATION CONTROL METHODS  
FOR AEROSTRUCTURES**

Grant Number: F49620-01-1-0208  
Grant Period: 28 Feb 2001 — 28 Feb 2004 (with no-cost extension through 28 Feb 2005)  
Grant Monitor: Dr. Clark Allred

**20050901 082**

## Abstract

The principal goals of this project were the further analysis and the experimental demonstration of the phenomenon of *nonlinear energy pumping* (targeted energy transfer), in which the vibration of a structure following a transient disturbance is irreversibly localized to a preferred subsystem, termed a nonlinear energy sink, and dissipated there. The occurrence of energy pumping depends on the essential nonlinearity of the sink stiffness; that is, this stiffness must be nonlinearizable, with no linear term in its force-displacement relation.

Two types of nonlinear energy sink (NES) have been investigated: Configuration I, in which the sink mass is coupled weakly and linearly to the primary structure and essentially nonlinearly to ground; and Configuration II, in which the coupling to the primary structure is essentially nonlinear but there is no connection of the sink to ground. The latter is obviously more practical for aerospace applications, and furthermore has been found to have greater potential for rapid energy transfer to the sink.

Much of the work done in this research program has focused on the dynamics of the NES interacting with a multi-degree-of-freedom linear structure. The topology of the underlying undamped nonlinear normal modes has been summarized in a frequency-energy plot, a schematic diagram which not only depicts the physics of transient resonant capture in these systems but allows the establishment of conditions under which energy pumping can occur (e.g., the initial deformation of the primary structure and the minimum initial energy). The potential for one sink to draw energy from several different modes of the linear structure to which it is attached, by resonating with each mode in turn, has been demonstrated by numerical simulation and through experiments.

We have advanced the analysis of these systems by refining the frequency-energy plots which summarize the nonlinear normal modes of one- and two-degree-of-freedom primary structures coupled to grounded and ungrounded energy sinks. This has led to improved understanding of  $m : n$  resonance capture in such systems, and to a much more detailed picture of the feasible periodic solutions. The role of nonlinear beating as a bridge from arbitrary initial conditions to the onset of energy pumping has been explored, and the influence of the parameters of the physical system has been explained analytically and verified experimentally.

Two- and three-degree-of-freedom systems comprising linear, one- or two-degree-of-freedom primary structures coupled to a nonlinear energy sink have been designed, numerically simulated, and fabricated. The primary and sink masses, each of the order of 1 kg, are supported and guided by a linear air track. Essential nonlinearity is achieved in the test rig by exploiting the geometrical nonlinearity of a transversely deflected wire, initially untensioned, which produces a nonlinearizable, cubic hardening restoring force. These springs have been calibrated for several wire spans and diameters. The remaining, linear portions of the test structures were characterized by modal analysis, following which the energy flow within the system was quantitatively measured.

We first obtained detailed, quantitative experimental data on the interaction of a nonlinear energy sink with a linear, single-degree-of-freedom primary structure. Excellent agreement was found between these experimental results and the output of a calibrated numerical simulation model in both the high- and low-energy regimes, where energy pumping does and does not occur, respectively. The primary structure was then extended to two DOF and the NES was shown to be capable of pumping energy from either structural mode following transient forcing of one primary mass. Other experiments have illustrated the resonance capture cascade, in which a nonlinear energy sink couples successively to multiple modes of the primary structure, and demonstrated the application of the NES to a continuous structure (a beam).

## 1 Objectives

The principal goals of this project were the analysis and experimental demonstration of the phenomenon of *nonlinear energy pumping*, in which the vibration of a structure following a transient disturbance is irreversibly localized to a preferred subsystem and dissipated there. These objectives are unchanged from those originally proposed.

## 2 Status of Effort

The understanding of multi-degree-of-freedom discrete systems (including modal series representations of continua) coupled to smoothly nonlinear sinks has been advanced through analysis and numerical simulation. Some damping is desirable in a practical device, but the dynamics of a system which may exhibit energy pumping can be explained and analyzed largely in terms of the nonlinear normal modes of the corresponding undamped, unforced system. The topology of the underlying undamped nonlinear normal modes has been summarized in a schematic diagram. Using a 2-DOF laboratory model, energy pumping has been shown experimentally to be robust and repeatable. This apparatus has been extended to examine MDOF structures in the laboratory.

A second configuration of the NES has been devised which eliminates the earlier requirement of a connection between the mass of the NES and ground. Not only is this a more practical design for installation on an aircraft or space structure, but this new NES configuration has been shown to be capable of pumping energy through additional, more efficacious mechanisms not found in the simpler NES investigated previously.

The goals of understanding and demonstrating energy pumping using relatively simple models and apparatus have been met. The potential of this technology is clear, and our focus is now shifting towards larger scale and more realistic applications.

## 3 Accomplishments and New Findings

### 3.1 Research Highlights


Advances made in each year of this research program are summarized briefly here. Much more detail may be found in the publications listed in a later section or in the previously submitted annual and interim progress reports.

#### 3.1.1 Year 1

- SDOF linear structure plus NES
  - Extensive numerical simulations were carried out in the course of designing an experimental rig consisting of a Configuration I (grounded) nonlinear energy sink coupled to a single-degree-of-freedom linear primary structure.
  - This apparatus was constructed and its various mass, damping, and linear and nonlinear stiffness parameters were identified.
  - Experiments demonstrated transient resonant captures between the two subsystems following loading of the primary structure.
  - Analysis of possible interactions between the sink and primary structure led to improved understanding of energy transfer mechanisms and the influence of system parameters and initial conditions on energy pumping performance.


#### 3.1.2 Year 2

- SDOF linear structure plus NES




**Figure 1.** One-dimensional air track installed in the laboratory.

- The topology of the nonlinear normal modes of the Configuration I system was fully described and summarized in frequency-energy plots depicting amplitude vs. energy or resonant frequency vs. energy.
- Simulations and experiments were begun to examine the effectiveness of the NES as a broad-band vibration absorber by driving this configuration with a random load.
- MDOF linear structure plus NES
  - The formulation of the equations of motion of a general linear system coupled to an essentially nonlinear energy sink, and their analysis by complexification and averaging, was completed.
  - The topology of the NNMs of this system was synthesized as was previously done for the SDOF structure and sink.
  - The possibility of resonance capture cascades, in which the sink resonates with two or more modes of the primary structure in turn, was demonstrated by simulation and the physics of this phenomenon were described in terms of the NNMs of the underlying undamped, unforced system.
  - The laboratory air track previously used to demonstrate energy pumping in a 2-DOF system was lengthened and otherwise improved. The new track is shown in Fig. 1.
- Use of non-smooth nonlinearities
  - Shock isolation through energy pumping in systems employing clearance (gap or vibro-impact) nonlinearities was investigated through extensive numerical simulations.
- Steady-state energy pumping
  - Localized NNMs were investigated for application in isolating substructures subject to periodic disturbances.




(a) Schematic of the masses, connections and transducers in the 2-DOF system.




(b) Two cars, representing the primary and sink masses, mounted on the air track.


**Figure 2.** Experimental apparatus.



(a) Directly excited linear subsystem.



(b) NES.



(c) Normalized dissipation in sink damper.

**Figure 3.** Example response when energy pumping occurs: experimental (solid line) and simulated (dashed line) acceleration time series.

- Analytical and numerical results showed these systems to be capable of a rich variety of steady-state responses.
- Good agreement was found between theory and experiment in a preliminary steady-state trial.

### 3.1.3 Year 3

- SDOF linear structure plus NES

- The existing experimental apparatus was refined (e.g., to further reduce unwanted friction between the moving masses and the air track during the initial portion of the transient response) and more completely characterized by dynamic tests and static measurements.
- Extensive experimental data were collected describing the transient input force and structural response of this system at both low and high energies. The experimental set-up is shown in Fig. 2.
- These experiments were compared to numerical simulations with excellent agreement, especially of the time evolution of the response signal envelopes. Examples of this agreement may be seen in Fig. 3.

- MDOF linear structure plus NES
  - Experiments were conducted in which a second degree of freedom was added to the primary structure of the system above in such a way that only one of the two primary masses was elastically coupled directly to ground. While it was straightforward to demonstrate energy pumping from the first (lower-frequency) natural mode of this structure to the sink, it proved difficult to excite the second (higher-frequency) mode at a sufficiently high amplitude.
  - Simulations indicated that coupling both masses of the primary system to ground by introducing an additional linear spring might result in a system in which both modes could be excited at levels sufficient to produce energy pumping.
  - The experimental rig was modified along these lines in an effort to demonstrate an energy pumping cascade, in which transient forcing or prescribed initial conditions lead to pumping from both modes in succession.
- NES Configuration II
  - A new arrangement of the elements of the nonlinear energy sink was devised, offering the following advantages:
    - \* Elimination of any direct connection of the sink to ground, making possible the construction of a modular NES to be attached to a primary structure at a single point.
    - \* Additional and more efficacious mechanisms for energy pumping than were found to exist in the grounded sink configuration previously studied.
  - Analysis and simulation of systems incorporating a sink of this new configuration included the examination of the potential of this device to suppress limit cycle oscillation of aircraft structures.

### 3.1.4 Year 4

- The role of  $m : n$  (i.e., non-1 : 1) resonance capture was analyzed and the results incorporated in the frequency-energy and nonlinear normal mode explanations of energy pumping.
- The importance of nonlinear beating in the response to arbitrary initial conditions was more completely explained, and the corresponding bridging orbits leading to one-way energy pumping were analyzed. Experiments clearly showed the transition from beating to pumping following a transient input.
- Experiments were performed with the new Configuration II sink.
- Additional experiments were performed in which the primary system was a 2-DOF linear structure or an Euler-Bernoulli beam. Good agreement with analysis and simulation was found.
- The existence of a resonance capture cascade, in which a single nonlinear energy sink interacted with multiple modes of the primary structure, was demonstrated experimentally.

## **4 Significance to the Field**

The analysis and simulation of two configurations of the nonlinear energy sink, including one in which the sink requires no connection to ground, has been expanded and corroborated by experiments. Experimental results have been found to agree well with simulation data and with analysis. Experiments continue with more complex primary structures, namely MDOF discrete structures and beams, results of which verify the existence of resonance capture cascades. These are necessary steps toward the practical application of the phenomenon to the reduction of the transient vibratory response of realistic structures. Numerous applications outside the laboratory, for example to aerospace and land vehicles and civil structures, are expected to follow once a firm basis for the technology has been established.

### **4.1 Relationship to Original Goals**

We found no cause to deviate from our original goals, defined in our proposal.

### **4.2 Relevance to the Air Force's Mission**

While continuing to develop our understanding of the energy pumping mechanism for simple systems, as demonstrated in analyses, simulations and laboratory experiments, we have proceeded with applications to structures with more complex configurations; the ultimate aim of this research is the design of passive nonlinear energy sinks in practical (realistic) flexible structures. This research will pave the way for a more complete understanding of the nonlinear energy pumping phenomena and their application to practical engineering systems. This is highly relevant to the mission of the Air Force, as it promises to provide a new, effective means of passive vibration isolation and attenuation in complex flexible structures of immediate importance, such as aircraft and spacecraft.

## **5 Potential Applications to Air Force and Civilian Technologies**

Immediate application of this technology lies in protection of flexible structures from localized transient forces and potentially unstable aeroelastic responses. The nonlinear energy sink (NES) is designed to quickly direct vibratory energy from the structure itself to the sink, where it can be optimally dissipated. The sinks themselves may even be designed to be sacrificial. Examples of applications include protection of large satellite-borne solar arrays from space debris, stabilization of aircraft- and spacecraft-borne mechanical systems, limit cycle oscillation (flutter) suppression, and shock isolation of sensitive avionics and airborne fire-control systems.

## **6 Personnel**

### **6.1 Supported Personnel**

- Prof. Lawrence A. Bergman, Principal Investigator
- Prof. Alexander F. Vakakis, Principal Investigator
- Dr. D. Michael McFarland, Senior Research Scientist
- Prof. Leonid Issakovich Manevitch, Co-Investigator
- Prof. Oleg Gendelman, Co-Investigator
- Prof. Yuri V. Mikhlin, Co-Investigator
- Mr. Christian John Hartwigsen, Graduate Assistant
- Mr. Young S. Lee, Graduate Assistant



- Mr. Jeffrey J. Kowtko, Graduate Assistant
- Mr. Darien L. Gipson, Undergraduate Assistant
- Ms. Amanda J. Kinney, Undergraduate Assistant
- Ms. Melonee M. Wise, Undergraduate Assistant

## 6.2 Other Personnel

- Dr. Gaetan Kerschen (Fulbright Fellow), University of Liege, Belgium
- Dr. Panagiotis Panagopoulos, National Technical University of Athens, Greece

## 7 Publications

- A. F. Vakakis, L. I. Manevitch, O. Gendelman and L. A. Bergman, "Dynamics of Linear Discrete Systems Connected to Local, Essentially Nonlinear Attachments," *Journal of Sound and Vibration*, 264(3):559–577, 2003.
- O. Gendelman, L. I. Manevitch, A. F. Vakakis and L. A. Bergman, "A Degenerate Bifurcation Structure in the Dynamics of Coupled Oscillators with Essential Stiffness Nonlinearities," *Nonlinear Dynamics*, 33(1):1–10, 2003.
- X. Jiang, D. M. McFarland, L. A. Bergman and A. F. Vakakis, "Steady State Passive Nonlinear Energy Pumping in Coupled Oscillators: Theoretical and Experimental Results," *Nonlinear Dynamics*, 33(1):87–102, 2003.
- A. F. Vakakis, D. M. McFarland, L. A. Bergman, L. I. Manevitch and O. Gendelman, "Isolated Resonance Captures and Resonance Capture Cascades Leading to Single- or Multi-Mode Passive Energy Pumping in Damped Coupled Oscillators," *ASME Journal of Vibration and Acoustics*, 126(2):235–244, 2004.
- A. F. Vakakis, L. I. Manevitch, A. I. Musienko, G. Kerschen and L. A. Bergman, "Transient Dynamics of a Dispersive Elastic Wave Guide Weakly Coupled to an Essentially Nonlinear End Attachment," *Wave Motion*, 41:109–132, 2005.
- D. M. McFarland, L. A. Bergman and A. F. Vakakis, "Experimental Study of Nonlinear Energy Pumping Occurring at a Single Fast Frequency," *International Journal of Nonlinear Mechanics*, 40(6):891–899, 2005.
- Y. S. Lee, G. Kerschen, A. F. Vakakis, P. Panagopoulos, L. A. Bergman and D. M. McFarland, "Complicated Dynamics of a Linear Oscillator with a Light, Essentially Nonlinear Attachment," *Physica D: Nonlinear Phenomena*, 204(1–2):41–69, 2005.
- F. Georgiadis, A. F. Vakakis, D. M. McFarland and L. A. Bergman, "Shock Isolation Through Passive Energy Pumping Caused by Non-Smooth Nonlinearities," *International Journal of Bifurcation and Chaos*, to appear.
- G. Kerschen, Y. S. Lee, A. F. Vakakis, D. M. McFarland and L. A. Bergman, "Irreversible Passive Energy Transfer in Coupled Oscillators with Essential Nonlinearity," *SIAM Journal on Applied Mathematics*, to appear.

- G. Kerschen, A. F. Vakakis, Y. S. Lee, D. M. McFarland, J. J. Kowtko and L. A. Bergman, "Energy Transfers in a System of Two Coupled Oscillators with Essential Nonlinearity: 1:1 Resonance Manifold and Transient Bridging Orbits," *Nonlinear Dynamics*, to appear.
- D. M. McFarland, G. Kerschen, J. J. Kowtko, L. A. Bergman and A. F. Vakakis, "Experimental Investigation of Targeted Energy Transfers in Strongly and Nonlinearly Coupled Oscillators," *Journal of the Acoustical Society of America*, to appear.

## 8 Interactions and Transitions

### 8.1 Conference Presentations

- A. F. Vakakis, D. M. McFarland and L. A. Bergman, "Energy Pumping Due to Resonance Capture in Coupled Nonlinear Oscillators," Presented at the 6th SIAM Conference on Applications of Dynamical Systems, Snowbird, Utah, 20–24 May 2001.
- X. Jiang and A. F. Vakakis, "Vibration Isolation Based on Strongly Nonlinear Mode Localization," EUROMECH 425: Symposium on Nonlinear Dynamics, Control and Condition Monitoring, Aberdeen, Scotland, 20–24 August 2001.
- A. F. Vakakis, D. M. McFarland and L. A. Bergman, "Vibration Suppression by Energy Pumping," Seminar/Workshop on Cooperative US-Europe Research in Sensors and Smart Structures Technology, Como, Italy, 12–13 April 2002.
- X. Jiang and A. F. Vakakis, "Vibration Isolation Based on Nonlinear Mode Localization," Proceedings of the 15th ASCE Engineering Mechanics Conference, Columbia University, New York, 2–5 June 2002, paper no. 333 (CD-ROM).
- D. M. McFarland, D. L. Gipson, A. F. Vakakis and L. A. Bergman, "Characterization of an Essentially Nonlinear 2-DOF Vibration Test Apparatus," Proceedings of the 15th ASCE Engineering Mechanics Conference, Columbia University, New York, 2–5 June 2002, paper no. 338 (CD-ROM).
- D. M. McFarland, A. F. Vakakis and L. A. Bergman, "Experimental Verification of the Performance of a Nonlinear Energy Sink," Proceedings of the 15th ASCE Engineering Mechanics Conference, Columbia University, New York, 2–5 June 2002, paper no. 339 (CD-ROM).
- D. M. McFarland, L. A. Bergman, A. F. Vakakis, L. I. Manevitch and O. Gendelman, "Energy Pumping into Passive Nonlinear Energy Sinks Attached to Forced Linear Substructures: Analytical and Experimental Results," 9th Conference on Nonlinear Vibrations, Stability, and Dynamics of Structures, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, 28 July–1 August 2002.
- A. F. Vakakis, L. I. Manevitch, O. Gendelman and L. A. Bergman, "Passive Nonlinear Energy Pumping in Coupled Oscillators," presented at the VIII International Conference on Recent Advances in Structural Dynamics, Southampton, UK, 14–16 July 2003.
- F. Georgiadis, A. F. Vakakis, D. M. McFarland and L. A. Bergman, "Shock Isolation Through Passive Energy Pumping in a System with Piecewise Linear Stiffnesses," 19th ASME Biennial Conference on Mechanical Vibration and Noise, Chicago, 2–6 September 2003. Proceedings, CD-ROM, paper no. DETC2003/VIB-48490.

- A. F. Vakakis, D. M. McFarland, L. A. Bergman, L. I. Manevitch and O. Gendelman, "Passive Vibration Control Through Nonlinear Energy Pumping," 19th ASME Biennial Conference on Mechanical Vibration and Noise, Chicago, 2–6 September 2003. Proceedings, CD-ROM, paper no. DETC2003/VIB-48532.
- X. Jiang, D. M. McFarland, L. A. Bergman and A. F. Vakakis, "Passive Nonlinear Energy Pumping in Coupled Oscillators: Steady State Results," 19th ASME Biennial Conference on Mechanical Vibration and Noise, Chicago, 2–6 September 2003. Proceedings, CD-ROM, paper no. DETC2003/VIB-48533.
- D. M. McFarland, L. A. Bergman and A. F. Vakakis, "Experimental Study of Nonlinear Energy Pumping Occurring at a Single Fast Frequency," 7th Conference on Dynamical Systems: Theory and Applications, Lodz, Poland, 8–11 December 2003. Proceedings, 613–620.
- D. M. McFarland, A. F. Vakakis and L. A. Bergman, "Experiments in Transient Nonlinear Energy Pumping in Vibrating Mechanical Systems," presented at the Department of Mechanical and Industrial Engineering, University of Thessaly, Volos, Greece, 3 March 2004.
- D. M. McFarland, A. F. Vakakis and L. A. Bergman, "Experiments in Transient Nonlinear Energy Pumping in Vibrating Mechanical Systems," presented at the Laboratoire de Techniques Aeronautiques et Spatiales-Vibrations et Identification des Structures, Universite de Liege, Liege, Belgium, 9 March 2004.
- D. M. McFarland, A. F. Vakakis and L. A. Bergman, "Experiments in Transient Nonlinear Energy Pumping in Vibrating Mechanical Systems," presented at the Structural Mechanics and Coupled Systems Laboratory, Conservatoire National des Arts et Metiers, Paris, France, 11 March 2004.
- A. F. Vakakis, D. M. McFarland, L. A. Bergman, L. I. Manevitch and O. V. Gendelman, "Nonlinear Normal Modes and Energy Pumping," EUROMECH Colloquium 457: Nonlinear Modes of Vibrating Systems, Frejus, France, 7–9 June 2004.
- D. M. McFarland, L. A. Bergman and A. F. Vakakis, "Experimental Nonlinear Energy Pumping," 10th Conference on Nonlinear Vibrations, Stability, and Dynamics of Structures, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, 25–29 July 2004.
- Y. Wang, D. M. McFarland, A. F. Vakakis and L. A. Bergman, "A Seismic Base Isolation System Employing Nonlinear Localization," Seventh International Conference on Motion and Vibration Control, St. Louis, Missouri, 8–11 August 2004. Proceedings, paper no. 182.
- Y. S. Lee, A. F. Vakakis, L. A. Bergman and D. M. McFarland, "Elimination of Limit Cycle Oscillation in a van der Pol Oscillator Using a Nonlinear Energy Sink," Third International Conference on Advances in Structural Engineering and Mechanics, Seoul, Korea, 2–4 September 2004.
- G. Kerschen, D. M. McFarland, J. J. Kowtko, A. F. Vakakis and L. A. Bergman, "Passive Energy Transfer and Dissipation for Isolation from Transient Broadband Disturbances," US-Korea Joint Seminar/Workshop on Smart Structures Technologies, Seoul, Korea, 2–4 September 2004.

## **8.2 Invited Lecture**

- Alexander F. Vakakis, "Passive Motion Confinement by Means of Nonlinear Energy Pumping in Systems of Coupled Oscillators," 15th Summer School on Nonlinear Dynamics, Chaos and Complexity, University of Patras, Greece, 19–30 August 2002.

## **8.3 Consultative and Advisory Functions**

- Presentation to Air Force Scientific Advisory Board biennial meeting, Wright-Patterson AFB, Ohio, 5 December 2001. D. M. McFarland, A. F. Vakakis and L. A. Bergman, "Vibration Suppression by Energy Pumping: An AFOSR Extramural Project," part of the presentation "AFOSR Structural Mechanics Program Support for the AFRL/VA Mission" by Daniel J. Segalman, Program Manager, AFOSR/NA, Air Force Research Laboratory.
- Presentation at Sandia National Laboratories, Albuquerque, New Mexico, 18 July 2002. L. A. Bergman, D. M. McFarland and A. F. Vakakis, "Passive Nonlinear Energy Pumping in Structures."
- Presentation at Eglin AFB, Florida, 15 December 2003. A. F. Vakakis, D. M. McFarland and L. A. Bergman, "State of the Art of Nonlinear Energy Pumping."
- Presentation at the Army Research Office, Research Triangle Park, North Carolina, 9 July 2004. L. A. Bergman, D. M. McFarland and A. F. Vakakis, "Nonlinear Energy Pumping: A New Method for Mitigating the Effects of High Energy, Short Duration Transient Loads."
- Presentation at Sandia National Laboratories, Albuquerque, New Mexico, 13 September 2004. A. F. Vakakis, L. A. Bergman, D. M. McFarland, Y. S. Lee, G. Kerschen, P. Panagopoulos and J. J. Kowtko, "Nonlinear Energy Pumping for Vibration Absorption and Aeroelastic Instability Suppression."

## **8.4 Workshop Participation**

- L. A. Bergman, D. M. McFarland and A. F. Vakakis, "Flutter Suppression by Means of Nonlinear Energy Sinks," presented at the AFOSR/AFRL Workshop on Nonlinear Aspects of Aeroelasticity and Related Structural Dynamics, Shalimar, Florida, 6–7 March 2003.

## **8.5 Transitions**

None to date.

## **9 New Discoveries, Inventions, or Patent Disclosures**

- Invention Disclosure TF02010, "Passive Energy Pumping from a Vibrating System to an Attached Nonlinear Sink," filed 8 February 2002 with the Office of Technology Management of the University of Illinois at Urbana-Champaign.
- Invention Disclosure TF03070, "Vibratory Response Reduction by Means of Ungrounded Nonlinear Energy Sinks," filed 27 June 2003 with the Office of Technology Management of the University of Illinois at Urbana-Champaign.
- Patent Application, "A Device, a System and a Method for Transferring Vibrational Energy," U.S. Serial No. 10/919,752, filed 17 August 2004.